



O-Two Oxygen Flow Controllers

Oxygen Therapy Treatment for Single Patient Incidents

O-Two Oxygen Flow Controllers

Oxygen Therapy Treatment for Single Patient Incidents

When you need to provide oxygen therapy the O-Two adjustable oxygen therapy flow controller provides high quality manufacturing and performance.

The O-Two adjustable oxygen therapy flow controller is a calibrated, 12-position, fixed orifice, non-gravity sensitive flow controller. The flow controller is available in a complete range of Chemetron, Ohio, female swivel DISS or 1/8 NPT female pipe inlet connections and DISS fitting valve outlet connections.

The flow controller is a lightweight, unibody, ergonomically designed assembly that can accommodate humidifiers.

Ideal for all applications where adjustable oxygen therapy is to be provided, the O-Two adjustable oxygen therapy flow controller is unbeatable for quality, size and performance.

Warranty: These products have a two-year warranty against manufacturer's defects.

Features

Outstanding impact resistant	
All-metal construction	
Large viewing window	
Ribbed control knob	
Positive 12 click-stop positions	

Specifications

Therapy Flow Option 1:	0, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 12, 15 (+/- 10%)	
Therapy Flow Option 2:	0, 1, 2, 3, 4, 6, 8, 10, 12, 15, 20, 25 (+/- 10%)	
Maximum Rated Input Pre	essure: 50 PSI	
Operating Temperature Ra	ange: -18 to 50°C (0 to 122°F)	
Storage Temperature Ran	ge: -40 to 60°C (-40 to 140°F)	
Size (excluding outlet and inlet fitting): (h x w) 2.0 x 1.37 in (h x w) 5.1×3.5 mm		
Weight:	4.0 oz / 0.1 kg	

Ordering Information

01FC0115D Oxygen Therapy Flow Controller

0-15 L/min with 12 settings (Various inlet fittings available. Please specify at time of ordering).

01FC0125D Oxygen Therapy Flow Controller

O-25 L/min with 12 settings (Various inlet fittings available. Please specify at time of ordering).



15PL1074 Rev. 9 10_16