



## MULTIPLE MODES, COMPACT, LIGHTWEIGHT, EASY TO USE

The e500 ventilator ushers in a “new era” in controlled ventilation for resuscitation and patient transport! These electronically controlled, pneumatically powered ventilators provide a range of ventilation solutions for resuscitation and transport in the pre-hospital and in-hospital healthcare professionals.

**SIMPLICITY** - The ventilation solutions offered by the e500 cannot be compared to any other products of its type. The units are self-contained and only require attachment to a regulated oxygen supply and a transport ventilation circuit for immediate use. The easily replaceable, long lasting (18 -24 hour) battery can be charged while inside the ventilator or can be removed for charging and quickly replaced by a fresh battery pack. The display lighting has adjustable brightness for easy visualization of the ventilator settings in any ambient light conditions. Designed for a range of patient sizes (from large adult to infant), the e500 comes in a very small and lightweight package.


**SAFETY** - The continuous monitoring of ventilation parameters ensures that the device is always fully functional and ready for immediate use. The wide range of both visual and audible alarms provides the healthcare professional with warnings of any changes in patient or device parameters.

Correction of any alarm is simple to achieve due to the compact and easy to operate control layout. The Intuitive Patient Apnea Backup (IPAB) mode provides additional security for the spontaneously breathing patient on CPAP by automatically commencing ventilations should their inspiratory efforts cease.

**FUNCTIONALITY** - The simplicity of operation of the e500 provides controlled ventilation for both resuscitation and transport with the minimum of control adjustments required for simple patient set up. The range of Tidal Volumes and ventilation rates offered provide improved patient care for all resuscitation and transport situations in the pre-hospital and in-hospital setting. The inclusion of ventilation modes for “mask or protected airway CPR”, with visual and audible prompts, adds another dimension to the application of these products not found on other ventilators.

**CONTROLLABILITY** - The e500 provides an “ease of use” concept that is second to none. These products are designed to speed up and simplify the initiation of ventilations by simply choosing the rate/volume. There are no multiple screens to scroll through to establish patient ventilation parameters. The units have an initial, pre-set, start-up mode requiring only the selection of patient size to begin ventilation.


**ECONOMY** - In addition to the patient care benefits, the e500 ventilator provides excellent low gas consumption and an extremely long battery operating time. This assists in providing controlled ventilation to the patient over an extended period, making the e500 ventilator ideal for long transports where both electrical and oxygen supplies are always a critical concern.



Start Screen



CPR Screen



Ventilation Screen



Ventilator Circuit

Transport Ventilator

Test Lung



**EASY TO USE**  
Simple Controls

**AFFORDABLE**  
Exceptionally Low Price

**LIGHTWEIGHT**  
2.4 kg

## SPECIFICATIONS

<b>POWER SOURCE</b>	Compressed Oxygen
<b>CIRCUIT CONTROL SOURCE</b>	Electric
<b>VENTILATION MODES</b>	SIMV, CPAP, Mask CPR (MCP), Intubated CPR (ICPR), Quick Start Mode, Manual, Intuitive Patient Apnea Backup (IPAB)
<b>PATIENT SIZE RANGE</b>	15 Kg to large Adult
<b>VENTILATION FREQUENCY/ TIDAL VOLUME (F/ML)</b>	12 preset Vt/BPM settings 100/20 to 650/10
<b>QUICK START MODE DEFAULT VT/BPM</b>	500/10
<b>MANUALLY TRIGGERED VENTILATION</b>	Yes
<b>I:E RATIO</b>	1:2
<b>PEEP (CM H2O)</b>	Adjustable 4 - 20
<b>CPAP (CM H2O)</b>	Adjustable 4 - 20
<b>O2 (%) (FIO2)</b>	60 or 100 (0.6 - 1.0)
<b>Pmax (CM H2O)</b>	10 - 80
<b>Pmin (CM H2O)</b>	0 - 20
<b>TRIGGER SENSITIVITY (L/MIN)</b>	3
<b>APNEA BACK UP TIME (SEC.)</b>	Adjustable 10 - 60
<b>BATTERY OPERATING TIME</b>	18 hours for default settings
<b>BUILT-IN BATTERY CHARGER</b>	Yes
<b>A/C POWER ADAPTER</b>	100-240VAC/ 19VDC, 4.74A
<b>PATIENT CIRCUIT</b>	O-Two electronic ventilator circuit
<b>MOUNTING BRACKET</b>	Multi-configuration bracket
<b>DISPLAY TYPE</b>	4.3" Color TFT Screen
<b>LIVE MONITORING</b>	Vm, vt, Paw (AV), PAW (Peak), F, BPM, Battery level
<b>REAL TIME WAVEFORM</b>	Selectable Pressure or Flow
<b>ADJUSTABLE DISPLAY BRIGHTNESS</b>	Yes
<b>PARAMETER SETTINGS</b>	Single, Multi Function Rotary Control
<b>LOCK KEY FUNCTION</b>	Yes
<b>PAUSE FUNCTION</b>	Yes
<b>ALARMS (VISUAL AND AUDIBLE):</b>	Gas Supply Pressure, Pmax, Pmin, Low Battery, BCI, Apnea, Leak, Vm min., Vm max.
<b>AUDIBLE SILENCE</b>	Yes, 120 seconds
<b>DIMENSIONS (MM)</b>	250 x 200 x 155
<b>WEIGHT (KG) WITH/WITHOUT BATTERY</b>	2.4 / 1.70



## ORDERING INFORMATION

- 01EVE500** - e500 Transport Ventilator  
Incl. Six-foot gas supply hose\*, Power supply\*, Ventilator Circuit and test lung.
  - 01EV7035** - "e" Ventilator Smart Mount
  - Multi-configuration Mounting Bracket**
  - 01EV7037** - "e" Ventilator Transport System  
Carry Frame and Ambulance Mounting Bracke
  - 01CV8030-Cs** - O-Two Single-Use six foot Electronic Transport Ventilator circuit  
Case/10
  - 01CV9100** - Battery Pack
  - 01CV8040-Cs** - Intake Filter Assembly  
Case/10
- \* Specify Country of Use at time of ordering

THIS PRODUCT HAS A TWO YEAR WARRANTY AGAINST MANUFACTURERS DEFECTS.