

O-Two Finger Tip Pulse Oximeter



PORTABLE, COMPACT AND COST-EFFECTIVE SpO₂ MONITORING ON THE MOVE

Designed for use in a wide range of environments — from pre-hospital emergency to hospitals and home health care — the O-Two fingertip pulse oximeter delivers exceptional performance at an affordable price.

This small, compact, simple, reliable and durable device greatly enhances patient care. With its six display modes and 10 brightness levels, the O-Two fingertip pulse oximeter is easy to read in any orientation and in any light condition. The graphic displays of SpO₂ waveform, heart rate bar graph plus the numeric displays of SpO₂ and heart rate provide the user with the information they require to assess the patient's condition. The low-voltage operation provides for a 30-hour operating time under normal conditions.

Designed to fit a wide range of patient sizes from pediatric to adult with minimal clamping pressure so as to maintain skin integrity and circulation, the O-Two fingertip pulse oximeter is an affordable adjunct for patient assessment and monitoring.



ORDERING INFORMATION

01MN1000 - O-Two Finger Tip Pulse Oximeter
Incl., carrying case with belt loop, lanyard and two (2) batteries (Case of 15)

SPECIFICATIONS

APPLICABLE POPULATION:	Adult, Pediatric
SpO₂ MEASUREMENT RANGE:	70-99% (Resolution 1%)
SpO₂ MEASUREMENT ACCURACY:	80-99%; +/- 2% 70-79%; +/- 3% 0-69%; unspecified
PULSE RATE MEASUREMENT RANGE:	30-235 BPM (Resolution 1 BPM)
PULSE RATE MEASUREMENT ACCURACY:	30-100; +/- 2 bpm 101-235; +/- 2%
DISPLAY TYPE:	Dual color OLED display
DISPLAY PARAMETERS:	SpO ₂ , Heart rate
DISPLAY TYPES:	Numeric, Pulse Bar, Plethysmogram
MODES:	Six display modes
BRIGHTNESS:	Adjustable 10 levels
VISUAL ALARM:	Battery-low indicator
DIMENSIONS:	(W X H X D) 2.3 x 1.3 x 1.3 in (W X H X D) 58 x 32 x 34 mm
WEIGHT (WITHOUT BATTERIES):	1 oz / 28 g
BATTERY TYPE:	2 x AAA alkaline or rechargeable batteries
OPERATION TIME:	Up to 30 hours for normal operation
OPERATING TEMPERATURE (APPROX.):	5 to 40°C (41 to 104°F)
STORAGE TEMPERATURE (APPROX.):	-10 to 40°C (14 to 104°F)
OPERATING HUMIDITY:	15-80%
STORAGE HUMIDITY:	10-80%
ELECTROMAGNETIC COMPATIBILITY:	This product complies with IEC60601-1-2 for electromagnetic compatibility Group 1 Class B
INTERFERENCE RESISTANCE CAPACITY AGAINST AMBIENT LIGHT:	Deviation is smaller than +/- 1% between values of oxyhemoglobin measured in natural lighting, indoor conditions and present lighting sources and those measured in a dark room

THIS PRODUCT HAS A TWO-YEAR WARRANTY AGAINST MANUFACTURERS DEFECTS.



www.otwo.com

rpe Road, Brampton, ON, Canada, L6T 5M4

Telephone: +1 905 792-OTWO (6896) N.A. Toll Free: +1 800 387 3405

Facsimile: +1 905 799 1339 Email: resuscitation@otwo.com

