

Multi Patient Unit



o_two controlled
ventilation™

OXYGEN THERAPY TREATMENT FOR SINGLE PATIENT AND MULTIPLE CASUALTY INCIDENTS

When multiple casualty incidents occur, EMS providers often find their resources stretched in terms of equipment as well as personnel. For incidents where a number of patients require oxygen therapy simultaneously, the O-Two multi patient unit meets the challenge.

With six 0-15 L/min adjustable therapy flow controls and the capacity to operate an automatic resuscitator or demand valve resuscitator from the 9/16 in DISS self-sealing outlet on the end of the unit, the flexibility offered by the compact O-Two multi patient unit is second to none.

The O-Two multi patient unit attaches to any oxygen regulator with a 9/16 in DISS outlet that supplies 50 PSI pressure, with a minimum output flow rate of at least 160 L/min.

ALL METAL CONSTRUCTION

SIX INDIVIDUAL ADJUSTABLE THERAPY FLOW CONTROLS EACH
PROVIDING A 0-15 L/min FLOW RATE

ONE 9/16 IN DISS SELF-SEALING OUTLET FOR THE ATTACHMENT OF AN
AUTOMATIC VENTILATOR OR DEMAND VALVE

TWENTY-FIVE FOOT SUPPLY HOSE IS STANDARD, ALLOWING
THE UNIT TO BE PLACED WHERE IT IS NEEDED SUPPLIED WITH
SIX ADULT MEDIUM CONCENTRATION OXYGEN

THERAPY FACEMASKS WITH SURE-FLOW TUBING



SPECIFICATIONS

INPUT PRESSURE	50 PSI
OPERATING TEMPERATURE	-18°C to 50°C (0°F to 122°F)
STORAGE TEMPERATURE	-40°C to 60°C (-40°F to 140°F)
RELATIVE HUMIDITY FOR STORAGE AND OPERATING USE	15 to 95%
INPUT CONNECTION	9/16 in DISS
OUTPUT CONNECTION	9/16 in DISS self-sealing outlet
THERAPY FLOW CONNECTIONS	Firtree
THERAPY FLOW RANGE	0, 0.5, 1, 2, 3, 4, 5, 6, 8, 10, 12, 15 L/min
WEIGHT (MULTI PATIENT UNIT ONLY)	19.2 oz / 0.45 kg (approx.)
DIMENSIONS (INCHES)	8.0 x 5.0 x 2.0 in (approx.)
DIMENSIONS (MILIMITERS)	203 x 127 x 50 mm (approx.)

ORDERING INFORMATION

01OR6304	Multi-Patient Unit (Services up to 7 Patients) complete with 25 Foot Supply Hose*, 6 Adjustable 0-15 L/min Flow Controls, 2 Self-Sealing DISS Outlets, 6 Medium Concentration Oxygen Masks with Tubing	Each
----------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------

THIS PRODUCT HAS A TWO YEAR WARRANTY AGAINST MANUFACTURERS DEFECTS.